

CHAIN BLOCK

DAESAN portable, light weight hand chain hoists are compact and provide a dependable working tool for industrial maintenance, construction sites, machine shops, and production situations where parts need to be positioned accurately but infrequently.

Covers: Protective steel covers can easily be removed for inspection and maintenance. Wheel cover & brake cover protect block from dust and rain.

Mechnical Load Brake: Can hold a capacity load stationary at any position.

Hooks: All hooks are drop forged, heat treated steel with spring type latches. Both hook rotates 360 for easy rigging.


Chain Guide: Allows smooth operation of load chain.

Load Sheaves: Deep cast pockets precisely fit the load chain. Load shafts are supported by prelubricated bearings for smooth operation.

Load Chain: Electric welded G80 alloy steel chain is heat treated for wear resistance and strength. Accurately and uniformly sized to seat properly in load sheaves.

- * Overload protection by slip clutch system (Option)
- For the last 3 decades DSN series had been sold over 1,000,000 units in Korea and overseas.





DSN TYPE

MODEL NO:		DSN0.5	DSN1	DSN1.5	DSN2N	DSN2	DSN3	DSN5	DSN7.5	DSN10	DSN15	DSN20	DSN25	DSN30	DSN40
Capacity(SWL)	Ton	0.5	1	1.5	2	2	3	5	7.5	10	15	20	25	30	40
Chainfall	No.	1	1	1	2	1	2	2	3	4	6	8	10	12	16
Standard lift	m	2.5	2.5	2.5	3	3	3	3	3.5	3.5	3.5	3.5	3.5	3.5	3.5
Load chain dia.	mm	6.3 x 19.1	6.3 x 19.1	7.1 x 21.0	6.3 x 19.1	7.9 x 23.0	7.1 x 21.0	9.0 x 27.0							
Hand chain	mm	5.0 x 22.8													
Net weight	Kg	11	12	14	18	22	23	41	63	86	131.5	209	393	536	696
Pulling efforts	Kg	18	33	34	33	34	35	39	40	41	41 x 2				
A (Dimension)	mm	147	147	147	150	184	147	185	185	185	212	212	388	426	502
В		145	145	164	179	187	206	258	367	367	745	873	798	798	798
С		310	330	360	430	380	480	620	720	820	850	970	1500	1870	1960
D		26	30	33	38	38	42	45	63	86	132	178	85	95	95